

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 June 2001 (21.06.2001)

PCT

(10) International Publication Number
WO 01/43649 A1

(51) International Patent Classification⁷: **A61B 17/068**,
17/128

(21) International Application Number: PCT/US00/34009

(22) International Filing Date:
15 December 2000 (15.12.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/172,426 17 December 1999 (17.12.1999) US

(71) Applicant: **FOGARTY, Thomas, J.** [US/US]; 3270
Alpine Road, Portola Valley, CA 94028 (US).

(72) Inventors: **HERMANN, George, D.**; 214A Grove Drive,
Portola Valley, CA 94028 (US). **DE LA PENA, Jose**;
Acueducto Rio Hondo #26, Los Virreyes, Mexico, D.F.
11000 (MX). **DE LA TORRE, Roger**; 2312 Longest

Drive, Wentzville, MO 63385 (US). **HOWELL, Thomas**;
567 Homer Avenue, Palo Alto, CA 94301 (US). **KHOURI,**
Roger; 328 Crandon Boulevard, #227, Key Biscayne, FL
33149 (US). **WILLIS, David**; 580 College Avenue, Palo
Alto, CA 94306 (US). **DREWS, Michael**; 4524 U Street,
Sacramento, CA 95817 (US).

(74) Agents: **KING, Cameron, A.** et al.; Morrison & Foerster
LLP, 755 Page Mill Road, Palo Alto, CA 94304-1018 (US).

(81) Designated States (*national*): CA, JP.


(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR USE IN MINIMALLY INVASIVE APPROXIMATION OF MUSCLE AND OTHER
TISSUE



Best Available Copy

(57) Abstract: Tissue approximation devices for the minimally invasive approximation of muscle or fascia, such as approximation of the rectus muscles in the abdomen (abdominoplasty), or hernia repair and other such applications using minimally invasive methods to access and perform the procedures thereby reducing or eliminating visible scars.

WO 01/43649 A1

METHOD AND DEVICE FOR USE IN MINIMALLY INVASIVE APPROXIMATION OF MUSCLE AND OTHER TISSUE

This application claims benefit of priority under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 60/172,426, filed December 17, 1999, which is incorporated herein in its entirety

BACKGROUND OF THE INVENTION

The present invention relates generally to medical apparatus and methods and more particularly to devices and methods for the minimally invasive approximation of muscle, fascia or other tissue such as approximation of the rectus muscles in the abdomen (abdominoplasty), hernia repair, closing fascial defects and other such applications where fascia or other tissue structures need approximating, that provide patient benefit using minimally invasive techniques that, among other benefits, reduce or eliminate visible scars.

In the case of diastasis of the rectus muscle and ventral hernias, separation of muscles and fascia from each other can occur over time due to stretching or weakening of tissue, resulting in protrusion at the region of separation of otherwise contained material, e.g. fat, tissue, or intestine. For example, during pregnancy or over time with weight gain, the rectus abdominus muscles, (the large muscles that run longitudinally along the abdomen from the torso to the groin of a human being), can diverge from each other, resulting in a flabby appearance or in some cases protrusion of accumulated fat or other structures through the separated region. Many people desire to undergo surgical repair of the separated muscles either to repair the herniation of material, or in less extreme cases, purely

for cosmetic reasons, sometimes in conjunction with liposuction or removal of excess skin and fatty tissue.

Historically, procedures such as abdominoplasty have been performed through a large open surgical incision in the abdomen, through which surgical tools are introduced to dissect away the subcutaneous tissue and fat from the abdominal fascia, and then directly reapproximating the medial borders of the rectus sheath, usually using sutures. Other methods for approximating fascia or otherwise joining body tissue are also known. For example, U.S. Patent No. 5,125,553 describes a surgical instrument for joining body tissue for stapling a hernial opening in internal tissues of a patient. U.S. Patent 4,127,227 describes a staple cartridge for applying staples to a large amount of fascia in a patient.

More recently, surgeons have performed abdominoplasty endoscopically by gaining access through a patient's umbilicus with the aid of a retractor and endoscope, and by making a smaller incision in the "bikini line" area to allow access for various surgical tools to dissect the muscles from the rectus fascia, as well as stapling tools to plicate the rectus fascia or suture the muscles together. As an example, U.S. Patent Nos. 5,329,943 and 5,655,544 describe an endoscopic procedure for performing an abdominoplasty through two small incisions at the umbilicus and the "bikini line" areas of the patient.

Approximation of the muscle and tissue is achieved by the use of a tenaculum (curved tip, sharp hemostat) and sutures or a stapling gun.

The abdominoplasty procedure can also be performed in conjunction with other procedures, such as liposuction, hernia repair or other reconstructive surgery.

While these techniques have been successful, there is a need for improved devices and methods for more efficiently performing procedures such as abdominoplasty that

further reduce post-procedure scarring and allow for more rapid and comfortable patient recovery. It would be desirable to have a system of devices that allowed a physician to directly access the treatment site without leaving any visible scarring. Furthermore, it would be desirable to have a system of devices and methods that allowed tissue

5 approximation procedures to be performed without the necessity of dissecting the subcutaneous tissue from the rectus fascia, thereby reducing trauma to the patient and speeding recovery time.

Such improved tools could access through a smaller incision, preferably at the umbilicus, where no visible scarring would ensue, and without the necessity of a second

10 incision for visualization tools or other device maneuvers. In addition, to speed recovery time it would be desirable to focus the penetration and pulling together of fascia, directly on the fascia sheaths with minimal disruption of the rectus muscles themselves. Furthermore, it would be desirable to have tools that allow approximation of fascia even in the absence of a continuous loop of fascia, or in the case where the posterior rectus sheath does not fully

15 extend or is not continuous in the area to be treated. This can be the case in the suprapubic region (below the umbilicus) where only the anterior portion of the rectus sheath extends.

Although such tools would be useful to approximate the tissue so that traditional suturing methods could be employed, it would also be desirable to have a system that included an implantable fastening member releaseably secured to the end of the tool for

20 placement once the desired location of approximation is attained. It would furthermore be desirable for such devices to generate sufficient force to bias the fascia together as well as to deploy the fastener device to secure the fascia in its new position. Additionally, improved methods would be desirable for accessing the points of approximation through

the rectus sheath of the abdominal rectus muscle, from within the fascia, as opposed to dissecting the subcutaneous tissue from the fascia more invasively and placing the approximating fasteners externally.

These and other objectives are met by the design and use of the various
5 embodiments of the present invention, as detailed herein.

SUMMARY OF THE INVENTION

According to the present invention, improved methods and apparatus are provided
10 for approximating tissue, fascia, muscle and the like. A first embodiment of the present invention provides a tissue approximating device or applicator tool, for use as a stand-alone device or tool or as part of a kit, for performing a minimally invasive abdominoplasty or similar procedure. The kit includes fastener devices, such as rivets or grommets, that can be placed from either side of a tissue surface while at the same time minimizing necessary
15 exposed tissue surface and incision length in the patient. The applicator tool has opposing surfaces or jaws that are mounted for movement toward and away from one another by actuation of a handle member.

In an exemplary use of the present invention, a surgeon makes an incision along the margins of the umbilicus and makes an incision into the medial border of the rectus fascia
20 of a patient and locates each jaw of the applicator tool into the envelope formed by the rectus sheath that surrounds the abdominus rectus muscles. This sheath encapsulates each length of abdominal muscle allowing each of the jaws to follow along the path formed between the sheath and the muscle, thereby minimizing the need for direct visualization once the tool is placed. Once located in their respective sheaths, the jaws of the tool can be

advanced to the location where the first fastener is to be placed. The device can also be palpated from the skin surface by the surgeon to determine the location of the distal end of the tool relative to the muscle separation which has been previously determined. After placement of the first fastener, the procedure is repeated until the separated length of the
5 abdominus rectus muscle has been approximated.

The present invention also incorporates an automated feature for releasing the fastening devices. The fastening devices can be formed in a series, such as in a cartridge, for easy loading into the jaws of the application tool. Alternatively, multiple fasteners can be deployed simultaneously from multiple deployment sites along the jaw of the applicator
10 tool. The fastening devices may be formed of various materials and construction, including varying sizes, shapes and compositions.

In a yet another embodiment, the applicator tool distal jaw section may be formed in a notched configuration having a reciprocal tooth and cavity arrangements such that when the jaws of the tool are brought together, the distal ends of each tip reciprocally engage the
15 other at the opposing notched or toothed section. The teeth contain recessed passageways, also referred to herein as "recesses" that allow the placement of a single fastening device in the longitudinal direction through tissue, as opposed to several fasteners deployed axially.

In a further embodiment, the applicator tool may be used simply to approximate the tissue or fascia without the secondary function of deploying a staple or other fastening
20 device. In this embodiment, once the tissue is approximated using the biasing tool of the present invention, standard, suturing techniques may be employed to secure the tissue.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an applicator tool according to the present invention having a handle end and a working end, and a hinged section therebetween;

FIG. 1A is an expanded view of the distal end of the applicator tool of FIG. 1 showing retaining elements on each jaw tip for retaining tissue fastening members and a tissue guard feature;

FIG. 1B shows an alternative embodiment of the applicator tool of FIG. 1 having a tissue engaging rod for engaging and manipulating fascia;

FIG. 2 illustrates the distal portion of the applicator tool of FIG. 1 where the components of a tissue fastening member are releaseably attached to the retaining elements;

FIG. 3A-3B illustrate different embodiments of a fastening member according to the present invention;

FIG. 4 illustrates a deployed tissue fastening member securing two approximated tissue layers together according to the teachings of the present invention;

FIG. 5A illustrates the anatomy of the normal relationship of rectus muscles within the rectus sheath;

FIG. 5B illustrates the anatomy of diastasis where the rectus muscles are separated;

FIG. 5C illustrates the anatomy of rectus muscles that have been reapproximated according to the present invention;

FIGS. 6 - 9 depict procedural steps of performing an abdominoplasty procedure according to the present invention using the applicator tool of FIG. 1;

FIG. 10 further illustrates an abdominoplasty procedure according to the present invention, including placement of the applicator tool jaws of FIG. 1 within the envelope of

the rectus sheath and the abdominal rectus muscle, and the placement of several fastening members to approximate the muscles;

FIG. 11 illustrates the placement of a surgical mesh reinforcing member over the site of repair and implanted fasteners;

5 FIG. 12 illustrates an alternative embodiment of the applicator tool of FIG. 1 having multiple retaining elements such that multiple fasteners can be delivered simultaneously by a single actuation of the tool;

FIG. 13A-13B illustrate an applicator tool according to a second embodiment of the invention having reciprocal teeth and cavities at the distal end of the tool that matingly
10 engage and enable a fastening member to be threaded through said teeth to longitudinally fasten together tissue clamped therebetween;

FIG. 14A-14C illustrate various alternative embodiments of the distal end of the applicator tool of FIG. 13, including embodiments having single and multiple teeth;

FIG. 15A-15D illustrate alternative embodiments of a fastening member to be used
15 in conjunction with the applicator tool of FIG. 13;

FIGS. 16 and 16A-16C illustrate a method of operating the applicator tool of FIG. 13 to approximate attenuated tissue surfaces;

FIG. 17 illustrates an embodiment of a fastening member according to the invention that that has been deployed to secure two approximated tissue layers;

20 FIG. 18 further illustrates the procedure of using the applicator tool of FIG. 13 to perform an abdominoplasty procedure including placement of the applicator tool jaws within the envelope of the rectus sheath and the abdominal rectus muscle, and placement of a longitudinal fastening member to secure the approximated muscles;

FIG. 19 illustrates a third embodiment of the present invention having a lever arm for engagement with fascia to facilitate approximation;

FIGS. 20-25 show embodiments of cartridge assemblies according to the present invention, where the assemblies house tissue fasteners; and

5 FIGS. 26-29 show a cartridge assembly of FIG. 20 being inserted onto a jaw of an applicator tool of the invention using alternative embodiments of an insertion tool according to the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 An exemplary applicator tool constructed in accordance with a first embodiment of the present invention is illustrated in Fig. 1. The applicator device 10 comprises a first handle portion 14 and a first jaw member 12, operatively connected to a second handle portion 13 and second jaw member 11 by hinging means 16. Hinging means 16 may be a fixed hinge, or in some cases a releasable hinge mechanism, such as a removable pin, to
15 allow the jaw members of the applicator tool to be placed separately within the rectus sheaths, and then linked together once they are placed at the point of the re-attachable hinge. The jaw members are likewise pivotally connected to their respective handle portions by hinging means 17.

 In operation, the movement of the handle portions 13,14 toward one another causes
20 force to be transmitted to the distal end of the jaw portions 11, 12 such that said jaw members move into contact with each other at their distal ends and/or continuing along the length of the jaw members depending on the jaw configuration and the number of fasteners to be deployed by a given actuation. Depending on the amount of tissue to be affected, the

force needed can vary. Specifically in the case of abdominoplasty, the force generated at the distal end of the applicator tool is estimated to be in the range of between 10 to 80 pounds preferably in the range of 20-40 pounds.

As seen in Fig. 2, jaw members 11 and 12 have distal ends 21 and 23 and proximal
5 ends 22 and 24. As illustrated retaining pin 25 is formed at distal end 21, for releasably securing a first fastening member 31 thereon. As depicted in Fig 1A, a tissue guard 15 is positioned on and extends distal end 21 to shield the tissue from any trauma from the retaining pin and rivet as the device is passed into the tissue. Corresponding thereto and further shown in Fig. 2, a gripping surface 27 is formed on distal end 23 for releasably
10 securing a second fastening member 33 thereon. Gripping surface 27 may be made of stainless steel or of a flexible material such as silicone, rubber or a thermoplastic elastomer. Alternatively, said gripping surface may be formed as a slot within the face of distal end 23, whereby said second fastening member is releasably retained thereon. Furthermore, distal end 23 may be provided with a through hole 29 adapted for receipt of retaining pin 25 when
15 jaws are in a closed position.

In a preferred embodiment, the first fastening member is a hollow rivet and the second fastening member is a washer with a hollow center configured to matingly engage with the rivet (as more fully depicted in Fig. 3) when distal ends 21 and 23 are brought together. Other types of fastening members will be readily apparent to one skilled in the
20 art. It is noted that depending on the desired configuration, the retaining member and gripping surface described above, can be mounted on either jaw of the application device.

An alternative embodiment of an application tool according to the present invention is shown in Fig. 1B. This tool is similar to that of Fig. 1A but further includes tissue

engaging rod 8. Tissue engaging rod 8 includes handle 6 at the proximal end and tissue engaging portion 4 at the distal end. The rod is threaded through eyelet 2. The eyelet diameter is larger than the diameter of the rod itself allowing for a wide range of motion of the rod, including motion between the jaw members and above or below the plane created by the jaw members. The invention also contemplates other known means of attaching the rod to the tool to provide for a similar range of motion, such as pivotally mounting the rod to the tool. In operation, as more fully described herein, the eyelet can act as a fulcrum point about which the rod can be moved to force tissue downward (or upward) out of the way of the jaw members in order to facilitate accuation of the tool.

Fig. 3A depicts the preferred embodiment of fastener 30a. In this embodiment, fastener 30a comprises a first fastening member 31a and a second fastening member 33a. As depicted herein, the first fastening member 3a is a rivet, having a disk portion 35a connected to a stem portion 34a and a hollow lumen therethrough.

The preferred dimensions of first fastening member 31a are .125" to .3121, and .032 to .093 for the stem. In the preferred embodiment, said stem member may be threaded, or otherwise fitted with an irregular surface.

The second fastening member 33a comprises a flat disc washer having a hollow center 36a and open slots 38a extending from said hollow center such that the circumference of the hollow center forms an irregular border.

The preferred diameter of second fastening 33a member is .125" to .312" (disc), .032 to .093 (hollow center), with slots 38a extending .010" to .050" from the center of disc 36. In operation, slots 38a facilitate the mating engagement of first and second fastening

members by frictionally engaging with the surface of stem 34a to form a permanent attachment to one another.

It should be noted that the fastener member can have several configurations depending on the application, for example discs 35 and 33 may be formed in an oblong, triangular or other shape to facilitate maximal interference with the target tissue once placed, as seen, for example, with fastener 306 shown in Fig. 3B. Furthermore, the fastener may be formed of stainless steel, Elgiloy, titanium or resorbable, implantable polymers. In an alternative embodiment as depicted in Fig. 12, multiple fastening members may be disposed along jaws 111, 112 of applicator tool 100 to allow simultaneous deployment of the fasteners through tissue following a single actuation of the applicator handle.

It is desirable that the fastening members be sheathed or protected during positioning of the fastening members prior to deployment. Among other reasons, such sheathing aids in ensuring that the fastening members are not dislodged from the applicator tool before reaching the desired deployment site. Such sheathing also protects tissue from unnecessary trauma, for example, due to contact with a retaining pin, prior to the jaw members reaching the desired site for deployment of the fastening members.

One such sheathing assembly is depicted in FIGS. 20-28. As depicted, fastener cartridge assembly 300 of FIG 20 includes cartridge body 310 and cartridge hood 340. Body 310 and hood 340 are typically formed of a durable plastic, such as a polycarbonate, that can be sterilized by autoclaving. Body 310 includes a base 312 having locking tabs 314 extending from the body. Driver body 316 extends away from the body in a direction generally opposite of the locking tabs. Retaining pin 325 extends from driver body 316 and receives spring clip 337 and rivet 331. Spring clip 337 can be made of, e.g., stainless steel

or plastic that can be deflected under load but that will return to its original shape once the load is released. Rivet 331 snaps into tab slots 339 of clip 337 and the rivet/clip assembly is then mounted onto retaining pin 325 which extends through the center bore of the rivet and corresponding hole of the clip.

5 Cartridge hood 340 is configured to extend at least partially over cartridge body 310 and includes a top portion 342 having opening 343 and sidewalls 344 that extend over at least a portion of the main body of cartridge body 310. Tab 345 is cut into sidewall 344 and includes a detent (not shown), which engages slot 319 of body 310. FIG. 21 shows cartridge 300 in a non-deployed condition, with the clip and rivet fastener assembly nested
10 inside cartridge hood 340 and the outer clip edges constrained by the interior shoulder of cartridge hood 340.

When sufficient force is exerted onto cartridge hood 340 against cartridge body 310, the detent of tab 345 releases from slot 319 and the cartridge hood moves toward cartridge body 310. As the driver body remains stationary, this movement of the cartridge hood
15 results in driver body 316 pushing rivet out of opening 343, as depicted in FIG. 22. When the force is released, the tension in spring clip operates to return the cartridge hood 340 to its original position, shown in FIG. 21.

FIGS. 23-25 depict cartridge 350 having a similar assembly of cartridge hood and cartridge body. Cartridge 350 includes cartridge hood 390 and cartridge body 360, and a
20 spring clip and fastening member assembly mounted on the body and nested within the hood 390. The difference in cartridge 350 is that clip 337 retains female washer 333 that fixedly mates with the stem of rivet fastener 331. Also, retaining pin 366 is deflectable, for example, it can be spring loaded or made of a deformable elastic material. When cartridge

300 and 350 are thus aligned opposite one another and are brought into contact, as happens when the cartridges are loaded onto the jaws of an actuator tool of the invention and the tool is actuated, the force exerted on the respective cartridge hoods moves the hoods relative to the cartridge bodies and rivet 331 and washer 333 are brought into contact and
5 fixedly mated, thereby securing any tissue located between the two cartridges. In this process, deflectable retaining pin 366 is deflected out of the way by retaining pin 325, thereby releasing the washer. When the actuating force is mated released, the fastener is deployed and the retainer springs operate to return the cartridge hoods to their original positions.

10 As shown in FIGS. 26-29, insertion tools 410 or 420 can be used to insert a cartridge into a recession 430 located on jaw 41 of an applicator tool. The insertion tools are configured to correspond to and releasably retain the cartridge hood. Under force, lock tabs 314 snap into place on the jaw, with flanges 315 corresponding to an undercut portion (not shown) of recess 430 located at the distal end of jaw 411. Insertion tool 420 of FIG.
15 29 includes pincer arms 422 that can be manually manipulated to move toward one another. These arms can correspond to notches (not shown) on lock tabs 314 of the cartridge. By engaging the notches with the pincer arms of the insertion tool and bringing the arms together, the lock tab arms can be moved toward one another to "pop" the cartridge out of the jaw after use.

20 Once implanted, as depicted in Fig. 4, deployed fastener 30a brings together the fascia and any other tissue that is placed between the first and second engaging members. As currently depicted, tissue layer A and tissue layer B are brought into approximation by fastener 30a.

Fig. 5A-5C illustrate the various anatomical locations depending on the status of approximation in each. Fig. 5A depicts a normal rectus abdominus section. Fig 5B depicts a diastasis of the abdominal rectus muscles, leaving an area of weakness (W) therebetween. Fig. 5C depicts the anatomical location of the rectus abdominus related to the placement of the fastening devices of the present invention.

The method of use of the preferred embodiment of the present invention is illustrated in Figs. 6-9. In Fig. 6, it should be noted that area (A) is drawn to have a transparent appearance to show the anatomical structures underneath comprising, rectus sheath 53 surrounding the rectus abdominus muscles 54. In practice of the invention, the only exposed incision location is at or near the patient's umbilicus or "belly button" in region 51. An umbilical incision 56 is made in the length of approximately 1 to 3 centimeters, such that once healed, the belly button will hide any scar that would be otherwise visible on the patient's abdomen. A larger incision may be made if additional tissue or fat removal is planned. Applicator tool 10 is placed into the incision as depicted in Fig. 7 and the jaw members are advanced between the rectus sheath and the abdominal rectus muscles to a point remote from the incision where the separated area to be treated is located.

As shown in Fig. 8, the applicator tool is then actuated as indicated by arrows C and D, bringing the rectus sheath together resulting in approximation of the abdominal rectus muscles.

Fig. 9 depicts insertion of the applicator tool in the opposite direction through the existing umbilical incision to approximate fascia in the upper abdomen.

Fig. 10 depicts a detailed view of the use of the application tool present invention.

Application tool 10 is inserted through the umbilical incision 56 and is advanced in the annular space created by the device 10 between the abdominal rectus muscle 54 and the rectus sheath 53. Fastening members are then installed by operation of the application tool
5 along the length of the separation to be treated, approximately every 1 to 3 centimeters. As the application tool is actuated the fastening member draws the fascia and other tissue together and secures the rectus sheath together, thereby pulling the abdominal rectus muscles into approximation with each other retaining pin 25 pieces the fascia, allowing the reciprocal fastening members to engage and fixedly mate. Optionally, as depicted in
10 Fig. 11, a prolene-type mesh member such as hernia mesh 60, can be placed across the approximated region to increase healing (scar tissue) at the fastener site, thereby relieving the stress on the fasteners and spreading it over the area of the mesh. The mesh can be either placed with fasteners or glued (not shown). The mesh can be placed over any number of fastening devices disclosed as part of the present invention.

15

As previously mentioned, application tool 100 of Fig. 1B can be used to facilitate approximation where there may be more extensive amounts of fascia or other tissue separating the abdominal muscles. In such situations, tissue engaging rod 8 can be manipulated to engage and force the fascia downward below the plane of the jaw members
20 and rectal muscles. This action both moves fascia out of the jaw path to facilitate acuation as well as create a pulling action transmitted by the fascia to the rectal sheaths that itself aids in bringing the rectal muscles into closer proximation.

A second embodiment of an applicator tool constructed in accordance with the present invention is illustrated in FIGS. 13A-13B. In this embodiment, applicator tool is provided with a distal tip having a reciprocating tooth/cavity configuration. The distal end of first jaw 112 and second jaw 111 are cut out in an alternating pattern to form teeth 130 and notches or cavities 136 that reciprocally engage one another when the jaws are brought together. As with the tool of Fig. 1A, the first and second jaws may be separately placed and then hooked together at the pivoting point. Between each tooth member 130, there is a cut away section forming a cavity 136 that is positioned relative to the tooth member of the opposing jaw to receive said opposing tooth member when the jaws of the applicator tool are in a closed position. At least one jaw of the applicator tool includes lumen 131 extending longitudinally along at least part of the length of the jaw length and terminating near the attachment point of handle member 14. A longitudinal fastener 132 can then be threaded through the lumen 131, using pusher member 133. As depicted in Fig. 13A, as lumen 131 extends up to the toothed section in the distal portion of the jaw, where it is axially aligned with passageway or recess 135 in teeth 130. In operation, this allows the fastener to remain in place following its longitudinal deployment through lumen 131 and recess 135 when the jaws are in a closed position. Each recess 135 opens toward the opposing jaw member which further allows the jaws to be reopened following longitudinal fastener deployment once the fastener 132 has been deployed through the toothed section of the jaw, just beyond the termination point lumen 131. Depending on the amount of tissue to be affected in one actuation of the applicator tool, the reciprocating tooth/cavity section length may vary, e.g., medium length (Fig. 14A), a single section (Fig. 14B) or maximal length (Fig. 14C).

Figs. 15A-15D depict various embodiments of longitudinal fastener 132. Fig. 15A shows a single longitudinal fastener 150, having a sharp distal end 151 for piercing tissue as it is advanced through lumen 131 and into the tissue clamped in the recess 135 and the cavity 136 of the clamp jaw. It may be further advantageous to provide an anchoring means
5 along the length of fastener 132 to ensure that the fastener remains localized in the tissue to be approximated once the fastener is deployed. Such anchoring structures 153 are depicted in Figs. 15B (constrained position) and 15C (deployed condition) as longitudinal slits 152 along the length of the fastener that are formed to spring out away from the main body of the fastener once placed. In an alternative embodiment, the anchoring structures may be
10 formed as protrusions 154 along the length of fastener 156 depicted in Fig. 15D. These protrusions may be flexible enough to deform upon deployment through the jaw through lumen, but resilient enough to expand and engage the tissue once fully deployed. The longitudinal fastening members may be formed of various materials, including spring steel, stainless steel, NiTi, Elgiloy or sufficiently rigid plastics or other implantable polymers.

15 Further, in yet an alternative embodiment, the longitudinal fastener may be formed of standard suture material. In this embodiment, the suture would be threaded through a needle member (not shown) and advanced along the jaw through lumen 131 and retracted once the suture was placed, leaving only the suture member in place at the end of the procedure.

20 In operation, and as shown in Fig. 16 applicator tool 100 is advanced through an umbilical incision and each jaw of the applicator tool is advanced within the annular space created by the tool between the abdominal rectus muscle and the rectus sheath as previously described in conjunction with Figs. 6-9. Fig. 18 shows in more detail the operation of this

method after insertion of tool into the rectus sheath and advancement to the point of the necessary reapproximation of tissue. In Fig. 16A the toothed sections 130 of the applicator tool jaws are aligned within rectus sheath 53 and actuated to move together, clamping the tissue of the rectus sheath 52 within cavities 136 of the toothed jaw, and the corresponding crowns of the teeth 130. Fig. 16B depicts the advancement of the longitudinal fastener 132 along lumen 131 of the jaw and through the recesses (not shown) and jaw cavities 136, engaging any tissue of the rectus sheath clamped therebetween. The jaws of the applicator tool are then released as illustrated in Fig. 16C, leaving the longitudinal fastener in place and approximating the rectus sheath. A cross section of the approximated tissue according to this secondary embodiment is shown in Fig. 17.

In some cases, it may be necessary to use a modified version of the applicator tool described herein as depicted in Fig. 19. In these cases the posterior rectus sheath portion is not coextensive with the anterior rectus sheath in the area to be treated, typically in the suprapubic region of the abdomen. Fig. 19 depicts an applicator tool having a lever arm 196 attached to or used in conjunction with said applicator tool, to assist in the desired tissue approximation in the absence of a continuous rectus sheath to lever the tissue together as previously described. As shown in Fig. 19, applicator tool 190 has a first handle 191 and a second handle 192 connected by a hinged section 193 to a first jaw 194 and a second jaw 195. Jaws 194 and 195 may be formed with a perpendicular section 188 and a parallel section 189 to allow the user increased leverage over the tissue. In addition, either as a separate tool, or a part of the applicator tool (e.g. joined at the hinge section 193) lever arm 196 is provided to assist the procedure. In operation, lever arm 196 can be placed longitudinally with respect to the rectus muscles and actuated in an upward movement

toward the anterior rectus sheath, creating an inverted IV, in the tissue and thereby tightening the fascia to form an edge over the anterior wall fascia and allowing the jaws to come together and secure the anterior fascial layer together.

Optionally in this configuration, the perpendicular portion of either the first jaw or
5 the second jaw may be detachable to allow for the jaws to be placed separately and then connected and the hinged section 193, once each is placed at the desired treatment site. Such a device and method may also be used anywhere in the body where you want to approximate fascia where it is not continuous along the length of the site to be treated.

While the above is a complete description of the preferred embodiments of the
10 invention, various alternatives, modifications, and equivalents may be used. Therefore, the above description should not be taken as limiting the scope of the present invention.

CLAIMS

We claim:

1. A tissue approximating device comprising:

first and second jaw members, said first and second jaw members being moveable toward and away from one another;

a first and second retaining means, said first and second retaining means being located generally opposite one another on said first and second jaw members, respectively;

and

first and second fastening members releasably secured to said first and second retaining means, respectively, said engaging means being configured such that when said first jaw member is moved toward said second jaw member, said first fastening member fixedly mates with said second fastening member.
2. The tissue approximating device of claim 1 wherein said first and second fastening members comprise a rivet and securing washer, respectively.
3. The tissue approximating device according to claim 1 further comprising a tissue engaging rod,

said tissue engaging rod having a tissue engaging portion that can extend generally parallel to said first and second jaw members and that is moveable from a first to second position.

4. The tissue approximating device of claim 3 wherein said tissue engaging rod is pivotally attached to said first and second jaw members.

5. A method of approximating the abdominal rectus muscles of a patient by adjoining the overlying tissue and rectus sheath surrounding said abdominal rectus muscles

comprising:

forming an incision in the abdomen of a patient;

providing an applicator tool having

first and second jaw members, said jaw members being moveable toward

one another upon actuation of said applicator tool, and

at least one pair of fastening members releasably attached to said first and

second jaw members, respectively, said fastening members being

configured to fixedly mate upon engagement with one another;

inserting said applicator tool into said incision;

advancing said jaw members along the length of the abdominal rectus muscles

within the rectus sheath;

actuating the applicator tool such that upon actuation said first and second jaw

members move toward one another and at least one of the fastening members pierces the

wall of the rectus sheath and fixedly mates with the other fastening member thereby

fastening said rectus sheath tissue therebetween; and

removing said applicator tool from the incision.

6. A method of approximating tissue according to claim 5 wherein said step of providing an applicator tool further comprises providing an applicator tool further having a tissue engaging rod having a tissue engaging portion that can extend generally parallel to said first and second jaw members and that is moveable from a first to second position; and further comprising the step of, after advancing the jaw members along the abdominal rectus muscles within the rectus sheath but prior to actuating the applicator tool, moving the lever arm such that tissue between said jaw members is engaged by the tissue engaging portion of said tissue engaging rod and is pressed downward.

7. A tissue approximating device comprising:

first and second jaw members moveable toward one another, said first and second jaw members having inner surfaces facing toward one another other, said inner surfaces of said first and second jaw members having at least one tooth member and at least one reciprocal cavity member, respectively, such that when the inner surfaces of said first and second jaw surfaces are moved toward one another said at least one tooth member on said first jaw member is received at least partially within said at least one reciprocal cavity member of said second jaw member.

8. The device of claim 7 wherein said first jaw member includes a lumen extending longitudinally through at least a portion of the first jaw member.

9. The device of claim 8 wherein said at least one tooth member of said first jaw member includes a recessed passageway extending longitudinally of the tooth member and

opening toward both proximal and distal ends of said first jaw member, said passageway being axially aligned with said lumen.

10. The tissue approximating device according to claim 7 further comprising a tissue engaging rod,

said tissue engaging rod having a tissue engaging portion that can extend generally parallel to said first and second jaw members and that is moveable from a first to second position.

11. The tissue approximating device of claim 10 wherein said tissue engaging rod is pivotally attached to said first and second jaw members.

12. A tissue approximating kit comprising:

a tissue approximating device having first and second jaw members moveable toward one another,

said first and second jaw members having inner surfaces facing toward one another other, said inner surfaces of said first and second jaw members having at least one tooth member and at least one reciprocal cavity member, respectively, such that when the inner surfaces of said first and second jaw surfaces are moved toward one another said at least one tooth member on said first jaw member is received at least partially within said at least one reciprocal cavity

member of said second jaw member, and a lumen extending longitudinally through at least a portion of the first jaw member; and an elongate fastening member adapted to be slidably received within the first jaw member lumen and the passageway of said tooth member.

13. The tissue approximating kit according to claim 12 wherein said fastening member further comprises an elongate body having restraining elements that extend from the body.

14. The tissue approximating kit according to claim 13 wherein said tissue approximating device further comprises a tissue engaging rod, said tissue engaging rod having a tissue engaging portion that can extend generally parallel to said first and second jaw members and that is moveable from a first to second position.

15. The tissue approximating kit of claim 14 wherein said tissue engaging rod is pivotally attached to said first and second jaw members of said tissue approximating device.

16. A method of approximating the abdominal rectus muscles of a patient by adjoining the overlying tissue and rectus sheath surrounding said abdominal rectus muscles comprising:

forming an incision in the abdomen of a patient;
providing an applicator tool having

first and second jaw members moveable toward one another, said first and second jaw members having inner surfaces facing toward one another other, said inner surfaces of said first and second jaw members having at least one tooth member and at least one reciprocal cavity member, respectively, said first jaw member further having a lumen extending longitudinally through at least a portion of said first jaw member, and said at least one tooth member further including a passageway extending longitudinally of the tooth member and opening toward both proximal and distal ends of said first jaw member, said recessed passageway being axially aligned with said lumen;

advancing said jaw members along the length of the abdominal rectus muscles within the rectus sheath;

actuating the applicator tool such that upon actuation, said first and second jaw members are moved toward each other, and at least one tooth member on said first jaw member is received at least partially within said at least one reciprocal cavity member of said second jaw member with a portion of said rectus sheath being located therebetween;

providing an elongate fastening member configured to be received through said first jaw member lumen;

advancing said fastening member through said first jaw member lumen and said tooth member passageway and through any tissue located therebetween.

17. A fastener cartridge for insertion onto a jaw member of a tissue approximation device, the fastener cartridge comprising:

a cartridge body, said cartridge body having a base configured for attachment to the jaw member and a driver member, said driver member having a fastener pin extending therefrom,

a retainer spring;

a fastner member releaseably secured to said retainer spring and to said fastner pin;

and

a cartridge hood, said cartridge hood having a top surface with an opening and sidewalls extending at least partially over said cartridge body such that said retainer spring, fastner member and driver member are disposed within said cartridge hood.

18. The fastener cartridge of claim 17 further comprising means for maintaining said cartridge hood and said cartridge body in a fixed relationship to one another.


19. The fastener cartridge of claim 17 further comprising a lock tab on said cartridge and reciprocal recess on said cartridge body, said lock tab engaging said recess to maintain said cartridge hood and said cartridge body in a fixed relationship to one another.

20. A tissue approximation kit comprising:

at least two fastner cartridges according to claim 17; and

a tissue approximating device having first and second jaw members being moveable toward and away from one another and recesses at the distal ends of the jaw members configured to retain said fastener cartridges.

21. The tissue approximation kit of claim 20 wherein at least one fastner cartridge contains a first fastening member and at least a second fastener cartridge contains a second fastening member, said first and second fastening members configured to fixedly engage one another.






FIG. 1B




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A



FIG. 5B






FIG. 5C









Fig. 8






FIG. 10




FIG. 11





FIG. 12









FIG. 13A

FIG. 13B










FIG. 15A




FIG. 15B




FIG. 15C






FIG. 15D

FIG. 16











FIG. 17

FIG. 18











FIG. 25




FIG. 27




FIG. 26




FIG. 28




FIG. 29

INTERNATIONAL SEARCH REPORT

In tional Application No

PCT/US 00/34009

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/068 A61B17/128

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 423 858 A (MASTRI DOMINICK L ET AL) 13 June 1995 (1995-06-13) column 3, line 4 -column 4, line 12; figure 1 column 4, line 60 -column 5, line 2; figure 4	1,2
A	---	7,12,20
X	US 5 591 206 A (MOUFARREGE RICHARD) 7 January 1997 (1997-01-07) column 6, line 6 - line 30; figures 1-7	1
A	---	7,12,20
X	US 5 423 856 A (GREEN DAVID T) 13 June 1995 (1995-06-13) column 3, line 34 -column 5, line 2; figures 1-6	7-9
A	---	12
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

21 March 2001

Date of mailing of the international search report

28/03/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ducreau, F

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 925 064 A (CARROLL MAUREEN E ET AL) 20 July 1999 (1999-07-20) abstract; figure 2 ---	7
A	EP 0 315 344 A (UNITED STATES SURGICAL CORP) 10 May 1989 (1989-05-10) the whole document ---	7,12
A	EP 0 169 044 A (ETHICON INC) 22 January 1986 (1986-01-22) page 11, line 33 -page 12, line 29; figure 8 ---	17,20
A	US 4 127 227 A (GREEN DAVID T) 28 November 1978 (1978-11-28) cited in the application abstract -----	17,20

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5423858	A	13-06-1995	NONE		
US 5591206	A	07-01-1997	NONE		
US 5423856	A	13-06-1995	AU	647521 B	24-03-1994
			AU	8456391 A	19-03-1992
			CA	2049123 A	14-03-1992
			DE	69120623 D	08-08-1996
			DE	69120623 T	28-11-1996
			EP	0477619 A	01-04-1992
			ES	2089073 T	01-10-1996
			JP	4226642 A	17-08-1992
			US	5489287 A	06-02-1996
			US	5573541 A	12-11-1996
			US	5292326 A	08-03-1994
			US	5389102 A	14-02-1995
US 5925064	A	20-07-1999	AU	714964 B	13-01-2000
			AU	3719697 A	21-01-1998
			BR	9710119 A	18-01-2000
			CA	2259475 A	08-01-1998
			EP	0920280 A	09-06-1999
			WO	9800068 A	08-01-1998
			AU	3513197 A	21-01-1998
			BR	9710113 A	18-01-2000
			CA	2259474 A	08-01-1998
			EP	0910294 A	28-04-1999
			WO	9800069 A	08-01-1998
EP 0315344	A	10-05-1989	AU	2461288 A	04-05-1989
			CA	1303934 A	23-06-1992
			JP	1190346 A	31-07-1989
			US	4950284 A	21-08-1990
EP 0169044	A	22-01-1986	AU	613056 B	25-07-1991
			AU	1871488 A	29-09-1988
			AU	604934 B	03-01-1991
			AU	1871588 A	29-09-1988
			AU	576597 B	01-09-1988
			AU	4489885 A	23-01-1986
			BR	8503367 A	08-04-1986
			CA	1259876 A	26-09-1989
			DE	3583073 D	11-07-1991
			HK	93791 A	29-11-1991
			IN	165375 A	07-10-1989
			JP	1917647 C	23-03-1995
			JP	6040879 B	01-06-1994
			JP	61106144 A	24-05-1986
			KR	9211010 B	26-12-1992
			SG	55091 G	23-08-1991
			US	4741336 A	03-05-1988
			ZA	8505332 A	25-02-1987
US 4127227	A	28-11-1978	CA	1109749 A	29-09-1981
			CA	1119072 A	02-03-1982
			DE	2743900 A	13-04-1978
			GB	1587849 A	08-04-1981
			GB	1587848 A	08-04-1981

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4127227 A		JP 1097124 C	14-05-1982
		JP 53047184 A	27-04-1978
		JP 56042938 B	08-10-1981
<hr/>			

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.